

STRETCH

CEILINGS & WALLS

STRETCH BV

Gentseweg 309 A3
9120 Beveren-Waas
Belgium

STRETCH Backlit - 307T/308T/309T

VAT: BE 0675.875.709

Mail: info@stretchgroup.be
Tel: +32 3 284 68 18
www.stretchplafond.be



Composition	Polyester knitted fabric coated with polyurethane (PU)
Width	250cm / 320cm / 515cm
Weight	200 gr/m2, +/- 10%
Thickness	0,4mm
Appearance	Matt, smooth and uniform
Colour	Translucent white
Strength	5 times greater than PVC film, doesn't crack CH : 5,5 daN; TR : 7,5 daN
Fire rating	B-s1,d0
Packaging	Cut to measure, In roll (50m)
Warranty	10 Year*
Reference	Net width
30725 - 30825 - 30925 (TD or TR)	250cm
30733 - 30833 - 30933 (TD or TR)	320cm
30752 - 30852 - 30952 (TD or TR)	510cm

Light transimtion	
307T	30%
308T	50%
309T	70%



Translu-
cent



Printable



Anti
Bacterial



Anti
Static



UV
Resistant



Water
Resistant



Light
Weight



Breathable



Long
Lasting



Eco
Friendly

*according to Stretch standard terms of sale





Maintenance

STRETCH technical fabrics are glassfiber fabrics coated with polyurethane, which under most circumstances protects them from absorbing odours. STRETCH fabrics are hydrophobic and require little or no maintenance.

If cleaning is required, it is recommended to use the STRETCH Cleaner and the STRETCH cleaning glove or a non-abrasive soft cloth in a white color. The method to follow is:

1. Spray some STRETCH Cleaner on the glove and dab the area immediately.
2. If the stain persists, it is possible to repeat the operation several times.
3. Alternatively, other pH-neutral cleaning agents can be used with a soft white cloth, provided it has first been tested on a scrap piece or on a non-visible area of the fabric.

Under no circumstance should sodium hypochlorite based solutions (bleach) be used.